


# STADIUM 60™

## TECHNICAL DATA

### PRODUCT SPECIFICATION

|                      |  |
|----------------------|--|
| <b>Product name:</b> | STADIUM 60                             |
| <b>Model:</b>        | STADIUM 60 - PU 14s                    |
| <b>Colour:</b>       | Emerald & Olive Bi-Color               |
| <b>Application:</b>  | Sport                                  |
| <b>Roll width:</b>   | 4.0m/2.0m/3.75m                        |
| <b>Roll Length:</b>  | According to request                   |
| <b>Warranty:</b>     | 5 years under PAVIGRASS warranty terms |



### YARN CHARACTERISTICS

|                        |              |
|------------------------|--------------|
| <b>Structure:</b>      | Diamond      |
| <b>Tape thickness:</b> | 400µm ± 10 % |
| <b>Tape width:</b>     | 1.0mm ± 10 % |
| <b>Composition:</b>    | PE           |
| <b>Dtex:</b>           | 14000 ± 10 % |

### CARPET CHARACTERISTICS

#### Turf

|                                    |                   |
|------------------------------------|-------------------|
| <b>Pile height:</b>                | 60 mm ± 5%        |
| <b>Gauge:</b>                      | 5/8 inch          |
| <b>Numbers of strands per tuft</b> | 14 strands        |
| <b>Stitches per 10cm:</b>          | 14 ± 10 %         |
| <b>Stitches per m2:</b>            | 8820 ± 10 %       |
| <b>Total yarn weight:</b>          | 1610 g/sqm ± 10 % |

#### Backing

|                             |                                   |
|-----------------------------|-----------------------------------|
| <b>Primary backing:</b>     | PP + Polyester fiber short-staple |
| <b>Weight:</b>              | 200 g/sqm                         |
| <b>Secondary backing:</b>   | PU                                |
| <b>Weight:</b>              | 850 g/sqm ± 10 %                  |
| <b>Total carpet weight:</b> | 2325g ± 10 %                      |

### INFILL REQUIREMENTS

#### Sand

|                             |                        |
|-----------------------------|------------------------|
| <b>Particle size range:</b> | 0.315-0.8mm            |
| <b>Bulk density:</b>        | 1.46 g/cm <sup>3</sup> |
| <b>Application rate:</b>    | 17 kg/m <sup>2</sup>   |

#### SBR

|                             |                         |
|-----------------------------|-------------------------|
| <b>Particle size range:</b> | 0.8 ~ 2.5 mm            |
| <b>Bulk density:</b>        | 0.400 g/cm <sup>3</sup> |
| <b>Application rate:</b>    | 15 kg/m <sup>2</sup>    |

#### Shock-pad

|  |   |
|--|---|
| <b>Shock-pad or elastic layer (if applicable):</b> | / |
|--|---|